YARIS COROLLA/MATRIX XD 2006 - 2015 2009 -

2008 - 2015



SCION Preparation

Part Number: PTR43-00072

Kit Contents

Item#	Quantity Reqd.	Description
1	1	Performance Air Filter
2	1	Warning Label
3		

Hardware Bag Contents

Item#	Quantity Reqd.	Description
1		
2		
3		

Additional Items Required For Installation

Item#	Quantity Reqd.	Description
1		
2		
3		

Conflicts

None

Recommended Tools

Notes	
Notes	
Notes	
Notes	
	Notes Notes

General Applicability

Corolla - 1.8L I4 \rightarrow 2009-Yaris - 1.8L I4 \rightarrow 2006-2015 Matrix - 1.8L I4 \rightarrow 2009-2013 Scion xD - 1.8L I4 \rightarrow 2008-2015

Recommended Sequence of Application

Item#	Accessory
1	
2	
3	

*Mandatory

Vehicle Service Parts (may be required for reassembly)

		() 1
Item #	Quantity Reqd.	Description
1		
2		
3		

Legend



STOP: Damage to the vehicle may occur. Do not proceed until process has been complied with.



OPERATOR SAFETY: Use caution to avoid risk of injury.



<u>CAUTION:</u> A process that must be carefully observed in order to reduce the risk of damage to the accessory/vehicle and to ensure a quality installation.



<u>TOOLS & EQUIPMENT:</u> Used in Figures calls out the specific tools and equipment recommended for this process.



<u>REVISION MARK:</u> This mark highlights a change in installation with respect to previous issue.



SAFETY TORQUE: This mark indicates that torque is related to safety.



YARIS COROLLA/MATRIX

XD

2006 -2009 -2008 - 2015 PERFORMANCE AIR FILTER

SCION Procedure

Care must be taken when installing this accessory to ensure damage does not occur to the vehicle. The installation of this accessory should follow approved guidelines to ensure a quality installation.

These guidelines can be found in the "Accessory Installation Practices" document.

This document covers such items as:-

- Vehicle Protection (use of covers and blankets, cleaning chemicals, etc.).
- Safety (eye protection, rechecking torque procedure, etc.).
- Vehicle Disassembly/Reassembly (panel removal, part storage, etc.).
- Electrical Component Disassembly/Reassembly (battery disconnection, connector removal, etc.).

Please see your Toyota or Scion dealer for a copy of this document.


1. Check the Contents and Prepare the Vehicle.


- (a) Check the box for contents and/or damage.
- (b) Use blankets to protect the front grille and driver-side front fender area.


Page 2 of 6 pages



SCION Procedure








2. Remove the OE Air Filter (2008 Scion xD shown).

- (a) Unlatch the two air filter housing clips (Fig. 2-1 through Fig. 2-3).
- (b) Disengage the air cleaner tabs and lift the air filter housing lid up to expose the factory air filter.
- (c) Remove the factory air filter from the air filter housing and discard the filter.

SCION Procedure



3. Install the TRD Air Filter (2008 Scion xD shown).


- (a) Insert the TRD air filter into the air filter housing with the deep side of the filter down in the housing (Fig. 3-1).
- (b) Position the filter so that the indexing protrusions on the top of the filter align with the reliefs in the air cleaner lid (Fig. 3-1).
- (c) Move the air filter housing lid into place.
- (d) Re-latch the two air filter housing clips (Refer to Fig. 2-1 through Fig. 2-3).
- (e) Use a lint free cloth and an approved cleaner such as 3M Prep Solvent 70 or similar to clean the air filter housing lid.
- (f) Use a lint free cloth and water to clean the same area as in Step 3(e).


YARIS COROLLA/MATRIX XD


2006 -2009 -2008 - 2015 **PERFORMANCE AIR FILTER**

SCION









- (g) Apply the TRD air filter warning label to the area pre-cleaned in Steps 3(e) and 3(f) (Fig. 3-2 through 3-4).
- (h) Remove the blankets from the front fender and grille area.

YARIS COROLLA/MATRIX 2006 -2009 - PERFORMANCE AIR FILTER

SCION

XD

2008 - 2015

Checklist - these points **MUST** be checked to ensure a quality installation.

Check:	Look For:
Accessory Function Checks	
Air filter housing lid	Reusable air filter warning label
	Air leaks/gaps
Vehicle Function Checks	
Vehicle Appearance Check	
After accessory installation and removal of protective cover(s), perform a visual inspection.	Ensure no damage (including scuffs and scratches) was caused during the installation process. (For PPO installations, refer to TMS Accessory Quality Shipping Standard.)